



1937 Mount Vernon Avenue, Pomona, California 91768-3312, USA 1-800-540-5823 or 1-909-865-3081 www.gwlinc.com | www.prolong.com

# SAFETY DATA SHEET

Issuing Date 29-Oct-2014

Revision Date 29-Oct-2014

**Revision Number** 0

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier	
Product Name	KOPR KOTE®
Other means of identification	
Product Code(s)	100
Synonyms	None
Recommended use of the chemical	and restrictions on use
Recommended Use	Lubricants, Greases and Release Products
Uses advised against	No information available
Supplier's details	
Manufacturer Address Jet-Lube, Inc. 4849 Homestead Rd. Suite 232 Houston, Texas 77028 TEL: 713-670-5700 (7:00 a.m 5:00)	p.m.)
Emergency telephone number	
Emergency Telephone Number	CHEMTREC: +1-703-527-3887 (INTERNATIONAL) 1-800-424-9300 (NORTH AMERICA)
	2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2

### Page 1/11

#### GHS Label elements, including precautionary statements

#### **Emergency Overview**

#### Warning Signal Word Hazard Statements • Causes skin irritation • Causes serious eye irritation • Causes eye irritation • C

#### **Precautionary Statements**

Prevention

- · Wash face, hands and any exposed skin thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.

#### **General Advice**

· Specific treatment is urgent (see supplemental first aid instructions on this label)

#### Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

#### Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

#### Storage

None

#### Disposal

None

### Hazard Not Otherwise Classified (HNOC)

Not applicable

#### Other information

20% of the mixture consists of ingredient(s) of unknown toxicity.

#### Page 2/11

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	74869-21-9	50-70	*
Graphite	7782-42-5	10-15	*
Copper	7440-50-8	8-13	*
Talc	14807-96-6	1-5	*
Limestone	1317-65-3	1-5	*
Molybdenum (IV) sulfide	1317-33-5	1-5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

#### Description of necessary first-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Drink plenty of water. Do not induce vomiting without medical advice. Clean mouth with water and afterwards drink plenty of water. If symptoms persist, call a physician.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

## **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

Water spray. Carbon dioxide (CO 2). Foam. Dry powder. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

#### Specific Hazards Arising from the Chemical

Burning produces obnoxious and toxic fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Heavy metal compounds

Page 3/11

#### **Explosion Data**

Sensitivity to	<b>Mechanical Impact</b>
Sensitivity to	Static Discharge

None. None.

#### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

 Personal Precautions
 Use personal protective equipment.

 Environmental Precautions
 Do not allow material to contaminate ground water system. Prevent product from entering drains. See Section 12 for additional Ecological Information.

 Methods and materials for containment and cleaning up
 Prevent further leakage or spillage if safe to do so.

## 7. HANDLING AND STORAGE

containers. Clean contaminated surface thoroughly.

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled

<b>Precautions</b>	for safe	handling
--------------------	----------	----------

Methods for Cleaning Up

Handling <u>Conditions for safe storage, includ</u>	Wear personal protective equipment. Ensure adequate ventilation. ing any incompatibilities
Storage	Keep container tightly closed in a dry and well-ventilated place. Keep in a bunded area
Incompatible Products	Strong oxidizing agents. Acetylene. Vinyl compounds.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Control parameters

#### **Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
---------------	-----------	----------	------------	--

#### Revision Date 29-Oct-2014

NFS-JLI-00105 - KOFK KUTE®			Revision Date 29-001-2014
Graphite 7782-42-	-	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 1250 mg/m <sup>3</sup>
5		synthetic	TWA: 2.5 mg/m <sup>3</sup> respirable dust
		TWA: 5 mg/m <sup>3</sup> total dust	
		synthetic	
		(vacated) TWA: 2.5 mg/m <sup>3</sup>	
		respirable dust natural	
		(vacated) TWA: 10 mg/m <sup>3</sup> total	
		dust synthetic	
		(vacated) TWA: 5 mg/m <sup>3</sup>	
		respirable fraction synthetic	
		TWA: 15 mppcf natural	
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA:	IDLH: 100 mg/m <sup>3</sup> dust, fume and
		1 mg/m <sup>3</sup> dust and mist	mist
		(vacated) TWA: 0.1 mg/m <sup>3</sup> Cu	TWA: 1 mg/m <sup>3</sup> dust and mist
		dust, fume, mist	TWA: 0.1 mg/m <sup>3</sup> fume
Talc 14807-96-	TWA: 2 mg/m <sup>3</sup>	(vacated) TWA: 2 mg/m <sup>3</sup>	IDLH: 1000 mg/m <sup>3</sup> containg no
6			asbestos and <1% quartz
			TWA: 2 mg/m <sup>3</sup>
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> respirable dust
		TWA: 5 mg/m <sup>3</sup> (vacated) TWA:	TWA: 10 mg/m <sup>3</sup> total dust
		15 mg/m <sup>3</sup> (vacated)	
		TWA: 5 mg/m <sup>3</sup>	
Molybdenum (IV) sulfide 1317-33-	TWA: 10 mg/m <sup>3</sup> Mo inhalable	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> Mo
5	fraction	(vacated) TWA: 10 mg/m <sup>3</sup> Mo	
	TWA: 3 mg/m <sup>3</sup> Mo respirable		
	fraction		<u> </u>

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

**Other Exposure Guidelines** 

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

#### Appropriate engineering controls

Engineering Measures	Showers	
	Eyewash stations	
	Ventilation systems	

#### Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection	Safety glasses with side-shields. Risk of contact, wear: Goggles. Impervious clothing. Impervious gloves. None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.
Hygiene Measures	When using, do not eat, drink or smoke. Remove and wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical State	Semi-fluid (gel)	Appearance	Copper Bronze
Odor	Petroleum like	Odor Threshold	No information available
<u>Property</u>	Values	<u>Remarks/ - N</u>	<u>Nethod</u>
рН	Neutral	None known	
Melting Point/Range	> 232 °C	None known	
<b>Boiling Point/Boiling Range</b>	< 316 °C	None known	
Flash Point	> 221 °C	None known	
Page 5/11			

Evaporation rate	<0.01	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	<0.01 kPa @ 20°C	None known
Vapor Density	>5 (air = 1)	None known
Specific Gravity	1.15	None known
Water Solubility	Insoluble in water.	None known
Solubility in other solvents	Largely.	None known
Partition coefficient: n-octanol/wa	terNo data available	None known
Autoignition Temperature	> 260 °C / >500 °F	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known
Flammable Properties	Not flammable	
Explosive Properties	No data available	
Oxidizing Properties	No data available	
5 1		
Other information		
other mormation		
VOC Contont (%)	None	
VOC Content (%)	INDITE	
VOC (g/l)	None	

## **10. STABILITY AND REACTIVITY**

#### **Reactivity**

No data available.

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### **Conditions to avoid**

Incompatible products.

### Incompatible materials

## Page 6/11

Strong oxidizing agents. Acetylene. Vinyl compounds.

#### Hazardous decomposition products

None known based on information supplied.

## **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

#### **Product Information**

Inhalation	None known.
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation.
Ingestion	Not an expected route of exposure. May be harmful if swallowed. Ingestion may cause
	gastrointestinal irritation, nausea, vomiting and diarrhea.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Lubricating greases	= 2280 mg/kg ( Rat )	-	-
A complex combination of			
hydrocarbons having carbon			
numbers predominantly in the range			
of C12 through C50. may contain			
organic salts of alkali metals,			
alkaline earth metals, etc.			

Symptoms related to the physical, chemical and toxicological characteristics

No information available.

Symptoms

No information available.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	Contains no ingredients above reportable quantities listed as a carcinogen.
Reproductive Toxicity	No information available. <b>STOT</b>
- single exposure	No information available. <b>STOT -</b>
repeated exposure	No information available. <b>Aspiration</b>

#### Numerical measures of toxicity - Product

Acute Toxicity20% of the mixture consists of ingredient(s) of unknown toxicity.The following values are calculated based on chapter 3.1 of the GHS document:LD50 Oral2606 mg/kg; Acute toxicity estimate

## **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

Hazard

Aquatic toxicity is unlikely due to low solubility. Based on available data, the classification criteria are not met

Lc50/48h/Acartia tonsa = >1000 mg/L EC50/72h/Skeletonema costatum = >1000 mg/L LC50/96h/Scophthalmus maximus = >1000 mg/L

#### Page 7/11

Sea sediment LC50/10d/Corophium sp. = 925-3502 mg/kg

oxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
>1001 mg/l	LC50 96 h: > 2000 mg/L (Salmo gairdneri)		
		>1001 mg/l LC50 96 h: > 2000 mg/L	Microorganisms           >1001 mg/l         LC50 96 h: > 2000 mg/L

Copper 7440-50-	EC50 96 h: 0.031 - 0.054	LC50 96 h: 0.0068 - 0.0156	-	EC50 48 h: = 0.03 mg/L
8	mg/L static	mg/L (Pimephales		Static (Daphnia magna)
	(Pseudokirchneriella	promelas)		
	subcapitata)	LC50 96 h: < 0.3 mg/L static		
	EC50 72 h: 0.0426 - 0.0535	(Pimephales promelas)		
	mg/L static	LC50 96 h: = 0.052 mg/L		
	(Pseudokirchneriella	flow-through		
	subcapitata)	(Oncorhynchus mykiss)		
		LC50 96 h: = 0.112 mg/L		
		flow-through (Poecilia		
		reticulata)		
		LC50 96 h: = 0.2 mg/L		
		flow-through		
		(Pimephales promelas)		
		LC50 96 h: = 0.3 mg/L		
		semistatic (Cyprinus carpio)		
		LC50 96 h: = 0.8 mg/L static		
		(Cyprinus carpio)		
		LC50 96 h: = 1.25 mg/L		
		static (Lepomis		
		macrochirus)		
Talc 14807-96-		LC50 96 h: > 100 g/L semi-		
6		static (Brachydanio		
-		rerio)		
Develotones and Deveed	ability Nie isterne ette	,		

Persistence and Degradability No information available.

**Bioaccumulation** 

No information available.

## Other Adverse Effects

No information available.

## **13. DISPOSAL CONSIDERATIONS**

Waste Disposal Methods	Dispose of in accordance with federal, state, and local regulations Where possible recycling is preferred to disposal or incineration.
Contaminated Packaging	Do not re-use empty containers.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Copper	Toxic

## **14. TRANSPORT INFORMATION**

## **15. REGULATORY INFORMATION**

#### International Inventories Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

#### **U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Copper	7440-50-8	8-13	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		Х	Х	

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

## U.S. State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

### U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Page 9/11					

Graphite	Х	Х	Х		Х
Copper	Х	Х	Х	Х	Х
Talc	Х	Х	Х		Х
Limestone	Х	Х	Х		Х

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION					
<u>NFPA</u>	Health Hazard 2	Flammability 1	Instability 0	Physical and Chemical Hazards -	
<u>HMIS</u>	Health Hazard 2	Flammability 1	Physical Hazard 0	Personal Protection X	

Revision Date 29-Oct-2014

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501		
Issuing Date	29-Oct-2014		
Revision Date	29-Oct-2014		
Revision Note	Initial Release.		

<u>General Disclaimer</u> The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet