1937 Mount Vernon Avenue, Pomona CA 91768 1-800-540-5823 / 1-909-865-3081

gwlinc.com



gas

1. Identification

Product identifier	A-151 (Aerosol)
Other means of identification	
Part Number	04320, M04320
Recommended use	A solvent degreaser designed for removing heavy residues from metal and other hard surfaces where reduced flammability, toxicity and environmental impact are concerns.
Recommended restrictions	None known.
Manufacturer/Importer/Supplie	er/Distributor information
Manufacturer	
Manufacturer	
Company name	ITW Pro Brands
Address	4647 Hugh Howell Rd.
	Tucker, GA 30084
Country	(U.S.A.)
	Tel: +1 770-243-8800
In Case of Emergency	1-800-424-9300 (inside U.S.)
	+001 703-527-3887 (outside U.S.)
Website	www.lpslabs.com
E-mail	lpssds@itwprobrands.com
2. Hazard(s) identification	n

SAFETY DATA SHEET

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed
Health hazards	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.
Storage	Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	Combustible.
Supplemental information	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%		
Distillates Petroleum Hydrotrea Light	ted	64742-47-8	60 - 70		
4. First-aid measures					
nhalation	Move to fresh air. Call a physician if symptom	is develop or persist.			
skin contact	No adverse effects due to skin contact are expected.				
ye contact	No specific first aid measures noted.				
ngestion	Not likely, due to the form of the product.				
Nost important symptoms/effects, acute and lelayed	Aspiration may cause pulmonary edema and pneumonitis.				
ndication of immediate nedical attention and special reatment needed	Provide general supportive measures and tre Symptoms may be delayed.	at symptomatically. Keep victi	m under observatior		
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.				
5. Fire-fighting measures					
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).				
Jnsuitable extinguishing nedia	Do not use water jet as an extinguisher, as this will spread the fire.				
Specific hazards arising from he chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.				
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.				
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been expose to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS st away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fit burn out.				
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Mov containers from fire area if you can do so without risk. In the event of fire and/or explosion do no breathe fumes.				
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode whe exposed to heat or flame. Combustible.				
6. Accidental release meas	sures				
Personal precautions, protective equipment and	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or				

Personal precautions, protective equipment and emergency procedures	Keep Unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Scoop up used absorbent into drums or other appropriate container. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat and sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Туре	Value	Form
PEL	5 mg/m3	Oil mist
Туре	Value	Form
TWA	5 mg/m3	Oil mist
No biological exposure limits noted for	or the ingredient(s).	
should be matched to conditions. If a or other engineering controls to main	pplicable, use process enclos tain airborne levels below rec	ures, local exhaust ventilation, ommended exposure limits. If
s, such as personal protective equipm	ient	
Wear safety glasses with side shield	s (or goggles).	
Wear appropriate chemical resistant	gloves.	
Wear suitable protective clothing.		
In case of insufficient ventilation, wear suitable respiratory equipment.		
Wear appropriate thermal protective clothing, when necessary.		
When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
	PEL Type TWA No biological exposure limits noted for Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to main exposure limits have not been estable s, such as personal protective equipm Wear safety glasses with side shields Wear appropriate chemical resistant Wear suitable protective clothing. In case of insufficient ventilation, weave Wear appropriate thermal protective When using do not smoke. Always of after handling the material and before	PEL 5 mg/m3 Type Value TWA 5 mg/m3 No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process encloss or other engineering controls to maintain airborne levels below recexposure limits have not been established, maintain airborne levels such as personal protective equipment Wear safety glasses with side shields (or goggles). Wear appropriate chemical resistant gloves. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipmed Wear appropriate thermal protective clothing, when necessary. When using do not smoke. Always observe good personal hygiene after handling the material and before eating, drinking, and/or smo

9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Clear water-white.
Odor	Characteristic.
Odor threshold	Not determined
рН	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	383 °F (195 °C)
Flash point	158.0 °F (70.0 °C) Tag Closed Cup
Evaporation rate	< 0.1 BuAc
Flammability (solid, gas)	Flammable gas.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	0.6 % Estimated
Flammability limit - upper (%)	20.4 % Estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 0.1 mm Hg @ 20 °C
Vapor density	6.1 (air = 1)
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not soluble in water
Partition coefficient (n-octanol/water)	>1
Auto-ignition temperature	> 381.2 °F (> 194 °C)
Decomposition temperature	Not available.
Viscosity	< 3 mm²/s @ 25 °C
Other information	
Explosive properties	Not explosive.
Heat of combustion	> 30 kJ/g
Oxidizing properties	Not oxidizing.
Specific gravity	0.84 - 0.86 @ 20 °C
VOC	0 % per U.S. State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis.	
Information on toxicological effe	ects	
Acute toxicity	May be fatal if swallowed and enters airways.	

Components	Species		Test Results	
Distillates Petroleum Hydrotreate	d Light (CAS 6474)		
<u>Acute</u>				
Dermal				
LD50	Rabbit		> 2000 mg/kg	
Inhalation				
Vapor				
LC50	Rat		> 4.5 mg/l, 4 Hours	
Skin corrosion/irritation	Prolonged skin	t may cause temporary irritatio	n.	
Serious eye damage/eye irritation	Direct contact v	es may cause temporary irritation	on.	
Respiratory or skin sensitizatio	on			
Respiratory sensitization	Not a respirato	Not a respiratory sensitizer.		
Skin sensitization	This product is	pected to cause skin sensitizati	ion.	
Germ cell mutagenicity	No data availat mutagenic or g		ents present at greater than 0.1% are	
Carcinogenicity	This product is	nsidered to be a carcinogen by	IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	Evaluation of Ca	enicity		
Not listed. OSHA Specifically Regulat	ed Substances (2	1910.1001-1050)		
Not regulated.		,		
US. National Toxicology Pr	rogram (NTP) Rep	Carcinogens		
Not listed.				
Reproductive toxicity	This product is	pected to cause reproductive of	r developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.	Not classified.		
Aspiration hazard	May be fatal if s	May be fatal if swallowed and enters airways.		
Chronic effects	Prolonged inha	Prolonged inhalation may be harmful.		
Further information	None known.			
12. Ecological informatio	n			
•				
Ecotoxicity			ardous. However, this does not exclude the rmful or damaging effect on the environment.	
Components		es	Test Results	
Distillates Petroleum Hydrotr	reated Light (CAS	47-8)		
Aquatic				
Fish		ow trout,donaldson trout hynchus mykiss)	2.9 mg/l, 96 hours	
Persistence and degradability				
Bioaccumulative potential				
Partition coefficient n-octa A-151 (Aerosol)	nol / water (log K	> 1		
Mobility in soil	No data availat	No data available.		
Other adverse effects	None known.			
13. Disposal consideration	ons			
Disposal instructions	under pressure		at licensed waste disposal site. Contents . Dispose of contents/container in accordance	
Local disposal regulations		e with all applicable regulations	5.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company. D003: Waste Reactive material			
Material name: A-151 (Aerosol)			SDS US	

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

, DOT	
DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	
DOT	





General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No
SARA 302 Extremely hazard Not listed.	lous substance
SARA 311/312 Hazardous chemical	Yes
SADA 212 (TDI reporting)	

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

China

n 112 Hazardous Air Pollutants (HAPs) List	
n 112(r) Accidental Release Prevention (40 CFR 68.130)	
Not regulated.	
California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.	
Inventory name	On inventory (yes/no)*
Australian Inventory of Chemical Substances (AICS)	Yes
Domestic Substances List (DSL)	Yes
Non-Domestic Substances List (NDSL)	No
	 n 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. California Safe Drinking Water and Toxic Enforcement Act of 1 is not known to contain any chemicals currently listed as carcin Inventory name Australian Inventory of Chemical Substances (AICS) Domestic Substances List (DSL)

Inventory of Existing Chemical Substances in China (IECSC)

Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date Revision date Version #	09-27-2015 09-14-2017 03
Disclaimer	ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.