

SAFETY DATA SHEET

1. Identification

Product identifier	LPS® 2 (Aerosol)	
Other means of identification		
Part Number	00216	
Recommended use	An industrial lubricant designed to displace moisture from equipment, provide heavy-duty lubrication and rust prevention.	
Recommended restrictions Manufacturer/Importer/Supplier/	None known. Distributor information	
Manufacturer		
Manufacturer		
Company name Address	LPS Laboratories, a division of Illinois Tool Wo 4647 Hugh Howell Rd. Tucker, GA 30084	orks, Inc.
Country	(U.S.A.) Tel: +1 770-243-8800	
In Case of Emergency	1-800-424-9300 (inside U.S.) +001 703-527-3887 (outside U.S.)	
Website E-mail	www.lpslabs.com sds@lpslabs.com	
2. Hazard(s) identification		
Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
Health hazarus		
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Contains gas ur irritation. Causes serious eye irritation. May ca	nder pressure; may explode if heated. Causes skin use drowsiness or dizziness.
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves. Wear eye/face protection.	
Response	for breathing. If in eyes: Rinse cautiously with if present and easy to do. Continue rinsing. Ca treatment (see this label). If skin irritation occu	I: Remove person to fresh air and keep comfortable water for several minutes. Remove contact lenses, ill a poison center/doctor if you feel unwell. Specific rs: Get medical advice/attention. If eye irritation if contaminated clothing and wash before reuse.
Matarial name: LPS@ 2 (Aarosol)		

Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC) Supplemental information	None known. None.

3. Composition/information on ingredients

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum, Hydrotea	ated	64742-47-8	70 - 80
Light			
Petroleum Oil		64742-52-5	10 - 20
Carbon Dioxide 4.		124-38-9	1 - 5
First-aid measures			
Inhalation	Remove victim to fresh air and keep at rest in breathing difficulties, oxygen may be necessar persist.		
Skin contact	Wash off with soap and water. Get medical att	ention if irritation develo	ps and persists.
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Get persists.		
ngestion	Call a physician or poison control center imme of medical personnel. Never give anything by	mouth to an unconscious	s person. If vomiting
Most important symptoms/effects, acute and delayed	occurs, keep head low so that stomach content doesn't get into the lungs. Dermatitis. Rash. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin irritation. May cause redness and pain.		
ndication of immediate nedical attention and special reatment needed	Provide general supportive measures and trea	at symptomatically.	
General information	Ensure that medical personnel are aware of the protect themselves. Call a POISON CENTER		
5. Fire-fighting measures			
Suitable extinguishing media	Powder. Alcohol resistant foam. Water. Water	spray. Dry chemicals. C	arbon dioxide (CO2).
Jnsuitable extinguishing nedia	Do not use water jet as an extinguisher, as this	s will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized contain flame.	er may explode when ex	posed to heat or
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equi with face shield, gloves, rubber boots, and in e		
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move without risk. Cool containers exposed to heat risk is involved. Containers should be cooled w For massive fire in cargo area, use unmanned not, withdraw and let fire burn out.	with water spray and ren with water to prevent vap	nove container, if no por pressure build up.
Specific methods	Use standard firefighting procedures and cons Move containers from fire area if you can do s flames with water until well after the fire is out. breathe fumes.	o without risk. Cool cont	ainers exposed to
General fire hazards	Extremely flammable aerosol.		
6. Accidental release mea	-		
Personal precautions,	Keep unnecessary personnel away. Keep pe	eople away from and up	wind of spill/leak. Keep out c
protective equipment and emergency procedures	low areas. Wear appropriate protective equip damaged containers or spilled material unles closed spaces before entering them. Local a cannot be contained. Use personal protectio	ss wearing appropriate p authorities should be adv	rotective clothing. Ventilate ised if significant spillages
Material name: LPS® 2 (Aerosol)	· ·		SDS

Methods and materials for Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no containment and cleaning up smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Use water spray to reduce vapors or divert vapor cloud drift. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. **Environmental precautions** Avoid discharge into drains, water courses or onto the ground. 7. Handling and storage Precautions for safe handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Conditions for safe storage, Level 3 Aerosol. including any incompatibilities Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may

flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits U.S. - OSHA Components Туре Value Form Distillates Petroleum, PEL 5 mg/m3 Oil mist Hydroteated Light (CAS 64742-47-8) Petroleum Oil (CAS PEL 5 mg/m3 Oil mist 64742-52-5) US. OSHA Table Z-1 Limits for Air Contami nants (29 CFR 1910.1000) Components Туре Value Carbon Dioxide (CAS PEL 9000 ma/m3 124-38-9) 5000 ppm ACGIH Components Form Type Value Distillates Petroleum, TWA 5 mg/m3 Oil mist Hydroteated Light (CAS 64742-47-8) TWA 5 mg/m3 Oil mist Petroleum Oil (CAS 64742-52-5) **US. ACGIH Threshold Limit Values** Components Value Type STEL 30000 ppm Carbon Dioxide (CAS 124-38-9) TWA 5000 ppm US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value

Material name: LPS® 2 (Aerosol)

Carbon Dioxide (CAS 124	1-38- STEL	54000 mg/m3
9)		30000 ppm
	TWA	9000 mg/m3
Biological limit values		5000 ppm
Biological limit values	No biological exposure limit	
Appropriate engineering controls	should be matched to condi ventilation, or other enginee exposure limits. If exposure acceptable level. Eye wash this product.	bically 10 air changes per hour) should be used. Ventilation rates tions. If applicable, use process enclosures, local exhaust ring controls to maintain airborne levels below recommended limits have not been established, maintain airborne levels to an facilities and emergency shower must be available when handling
Individual protection measures, Eye/face protection	Wear safety glasses with side s	
Skin protection	Wear salely glasses with side s	silieids (of goggies).
Hand protection	Chemical resistant gloves are r	ecommended.
Other	Wear suitable protective clothin	g.
Respiratory protection	In case of insufficient ventilation	n, wear suitable respiratory equipment.
Thermal hazards	Not applicable.	
General hygiene considerations	as washing after handling the n	r smoke. Always observe good personal hygiene measures, such naterial and before eating, drinking, and/or smoking. Routinely ive equipment to remove contaminants.
9. Physical and chemical p	properties	
Appearance	Liquid.	
Physical state	Gas.	
Form Color	Aerosol.	
Odor	Brown	
Odor threshold	Slight petroleum odor, Cherry Not established	
pH		
Melting point/freezing point	Not applicable < -58 °F (< -50 °C)	
Initial boiling point and boiling	383 °F (195 °C) @ 101 kPa	
range		
Flash point	174.2 °F (79.0 °C) Tag Closed	Cup (dispensed liquid)
Evaporation rate	< 0.1 BuAc	
Flammability (solid, gas) Upper/lower flammability or expl	Flammable gas.	
Flammability limit - lower (%)	0.6 %	
Flammability limit - upper (%)	7 %	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	< 0.05 mm Hg @ 20°C (dispens	sed liquid)
Vapor density	4.7 (air = 1)	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	< 3 %	
Partition coefficient (n- octanol/water)	< 1	
Auto-ignition temperature	> 442.4 °F (> 228 °C)	
Decomposition temperature	Not established	
Viscosity	< 7 cSt	

Material name: LPS® 2 (Aerosol)

Viscosity temperature	77 °F (25 °C)
Other information	
Heat of combustion	> 30 kJ/g
Percent volatile	92 - 95 %
Specific gravity	0.82 - 0.86 @ 20°C
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Skin contact Causes skin irritation. Eye contact Causes serious eye irritation. Ingestion May cause discomfort if swallowed. Symptoms related to the Irritating to eyes, respiratory system and skin. Symptoms may include stinging, tearing, redness, physical, chemical and swelling, and blurred vision. Exposure may cause temporary irritation, redness, or discomfort. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. toxicological characteristics Information on toxicological effects

Components	Species	Test Results
Distillates Petroleum, Hydroteatec Acute	Light (CAS 64742-47-8)	
Dermal LD50		> 2000 ma/ka
		> 2000 mg/kg
Inhalation	Rabbit	> 2000 mg/kg, 24 Hours
LC50	Cat Rat	> 6.4 mg/l, 6 Hours > 7.5 mg/l, 6 Hours
		> 4.3 mg/l, 4 Hours
		> 0.1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Petroleum Oil (CAS 64742-52-5)		
Acute		
Dermal		
LD50		> 2000 mg/kg
	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	2.18 mg/l, 4 Hours
<i>Oral</i> LD50		
	Rat	5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Material name: LPS® 2 (Aerosol)		

Respiratory or skin sensitization Respiratory sensitization Skin sensitization	Not a respira	atory sensitizer. is not expected to cause skin sensitiza	Acute toxicity tion.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	-	is not considered to be a carcinogen b	y IARC, ACGIH, NTP, or OSHA.
	Narcotic effe	-	
OSHA Specifically Regulate	d Substances	(29 CFR 1910.1001-1050)	
Not listed.		(,	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity -	Narcotic effe	ects.	
single exposure Specific target organ toxicity - repeated exposure	Based on av	ailable data, the classification criteria a	re not met.
Aspiration hazard	Not likely, du	ue to the form of the product.	
Chronic effects	Prolonged in	halation may be harmful.	
12. Ecological information			
Ecotoxicity	The product		ardous. However, this does not exclude the armful or damaging effect on the environment.
Components		Species	Test Results
Distillates Petroleum, Hydrote Aquatic	ated Light (CA	S 64742-47-8)	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Persistence and degradability		ly biodegradable.	
Bioaccumulative potential	Not available	2.	
Partition coefficient n-octan LPS® 2 (Aerosol)	ol / water (log	Kow) < 1	
Mobility in soil	No data ava	ilable.	
Other adverse effects	None known		
13. Disposal consideration	IS		
Disposal instructions	Consult auth	•	pressure. Do not puncture, incinerate or crush
Local disposal regulations			cal/regional/national/international regulations.
Hazardous waste code	-	ccordance with all applicable regulation Reactive material	5.
Waste from residues / unused			pty containers or liners may retain some
products		dues. This material and its container mu	ist be disposed of in a safe manner (see:
Contaminated packaging	Since emptie		aste handling site for recycling or disposal. e, follow label warnings even after container is
14. Transport information			
DOT			
UN number	UN1950		
UN proper shipping name Transport hazard class(es)	Aerosols, fla	mmable	
Class	2.1		

Material name: LPS® 2 (Aerosol)

Environmental hazards	
Marine pollutant	No
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
IATA	None
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
01000	
Subsidiary risk	-
Label(s)	
	licable. Environmental
hazards No.	
ERG Code	
Special precautions for use	er Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	instructions, SDS and emergency procedures before handling.
Other information Passenger and cargo	
Other information Passenger and cargo aircraft	instructions, SDS and emergency procedures before handling. Allowed.
Other information Passenger and cargo	instructions, SDS and emergency procedures before handling.
Other information Passenger and cargo aircraft Cargo aircraft only	instructions, SDS and emergency procedures before handling. Allowed.
Other information Passenger and cargo aircraft Cargo aircraft only IMDG UN number	instructions, SDS and emergency procedures before handling. Allowed. Allowed. UN1950
Other information Passenger and cargo aircraft Cargo aircraft only IMDG	instructions, SDS and emergency procedures before handling. Allowed. Allowed.
Other information Passenger and cargo aircraft Cargo aircraft only IMDG UN number UN proper shipping name	instructions, SDS and emergency procedures before handling. Allowed. Allowed. UN1950
Other information Passenger and cargo aircraft Cargo aircraft only IMDG UN number UN proper shipping name Transport hazard class(es)	instructions, SDS and emergency procedures before handling. Allowed. Allowed. UN1950 AEROSOLS, flammable
Other information Passenger and cargo aircraft Cargo aircraft only IMDG UN number UN proper shipping name Transport hazard class(es) Class	instructions, SDS and emergency procedures before handling. Allowed. Allowed. UN1950 AEROSOLS, flammable
Other information Passenger and cargo aircraft Cargo aircraft only IMDG UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk	instructions, SDS and emergency procedures before handling. Allowed. Allowed. UN1950 AEROSOLS, flammable 2.1
Other information Passenger and cargo aircraft Cargo aircraft only IMDG UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s)	instructions, SDS and emergency procedures before handling. Allowed. Allowed. UN1950 AEROSOLS, flammable 2.1 - 2.1
Other information Passenger and cargo aircraft Cargo aircraft only IMDG UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group	instructions, SDS and emergency procedures before handling. Allowed. Allowed. UN1950 AEROSOLS, flammable 2.1 - 2.1
Other information Passenger and cargo aircraft Cargo aircraft only IMDG UN number UN proper shipping name Transport hazard class(es) Class Subsidiary risk Label(s) Packing group Environmental hazards	instructions, SDS and emergency procedures before handling. Allowed. Allowed. UN1950 AEROSOLS, flammable 2.1 - 2.1 Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Not listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories Immediate Hazard - Yes Delaved Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous Yes chemical SARA 313 (TRI reporting) Not regulated. Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not regulated. Safe Drinking Water Act Not regulated. (SDWA) US state regulations US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed. **US. Massachusetts RTK - Substance List**

Carbon Dioxide (CAS 124-38-9)

US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (CAS 124-38-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Dioxide (CAS 124-38-9)

US. Rhode Island RTK Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name
----------------------	----------------

Material name: LPS® 2 (Aerosol)

On inventory (yes/no)*

SDS US 8/9

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	09-22-2014
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Product Uses Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties Ecological Information: Ecotox Property Data Transport Information: Proper Shipping Name/Packing Group Regulatory Information: United States HazReg Data: North America GHS: Classification