



1937 Mount Vernon Avenue, Pomona, California 91768-3312, USA 1-800-540-5823 or 1-909-865-3081 www.gwlinc.com | www.prolong.com

Issuing Date 05-May-2015

Revision Date 22-June-2015

SAFETY DATA SHEET Revision Number 1

U

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier	
Product Name	AFMT Anti-Friction Metal Treatment
Other means of identification	PSL10010, PSL10020, PSL10225, PSL10040
Synonyms	None
Recommended use of the chemical	and restrictions on use
Recommended Use	Hydraulic Systems, Power Transmission Equipment, Machine Tools, Heavy Chains and Pumps, Compressors, Generators and Pumps, Ball and Roller Bearings, Mining and Smelter Equipment, Gear Boxes, Injection Molding Machines, Railroad Equipment, Refineries and Oil Field Equipment, Paper and Pulp Mills.
Uses advised against	No information available
Details of the supplier of the safety	data sheet
Supplier Name Supplier Address	GoldenWest Lubricants, Inc. 1937 Mount Vernon Avenue Pomona, CA 91768 US
Supplier Phone Number	Phone:909-865-3081 Fax:909-865-4467
Supplier Email Emergency telephone number	info@gwlinc.com
Chem-Trec(US & Canada) Chem-Trec (International)	Phone: 800-424-9300 Phone: 703-527-3887 (Collect)






2. HAZARDS IDENTIFICATION

Classification

Not classified

GHS Label elements, including precautionary statements



Precautionary Statements - Prevention

Obtain special instructions before use. Do not breathe mist or vapor. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment.

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention. Collect spillage.

Precautionary Statements - Storage

Store away from incompatible materials.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified (HNOC)

None known.

Unknown Toxicity

1.37% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Harmful to aquatic life with long lasting effects.

Interactions with Other Chemicals

No information available.





3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Supplier Trade Secret	Proprietary	60 - 80	*
Petroleum distillates, hydro treated heavy paraffinic	64742-54-7	10 - 30	
Supplier Trade Secret	Proprietary	1 - 5	*
		10	

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General Advice

Note: When using this product in high pressure equipment - Accidental high velocity dermal injection of this material requires immediate medical attention.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention immediately if symptoms occur.

Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion

Call a physician or poison control center immediately. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

No information available.

Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Treat symptomatically. Keep victim under observations. Symptoms may be delayed.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

No information available.

Uniform Fire Code

Combustible Liquid: III-B

Hazardous Combustion Products

Normal combustion forms carbon dioxide and water vapor, and may produce oxides of carbon, sulfur hydrogen chloride and





nitrogen. Incomplete combustion can produce carbon monoxide.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For Personal protection, see section 8 of the SDS.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

Methods and material for containment and cleaning up

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Provide adequate ventilation. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

Incompatible Products

Oxidizing agent.





8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydro treated	TWA: 5 mg/m ³ , as oil mist,	TWA: 5 mg/m ³ , as oil mist,	
heavy paraffinic	mineral	mineral	
64742-54-7	STEL: TWA: 10 mg/m ³ , as oil		
	mist, mineral		

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health.

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d. 962 (11th Cir. 1992) See section 15 for national exposure control parameters.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tight sealing safety goggles.

Skin and Body Protection

Wear protective gloves and protective clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Thermal Hazards

Wear appropriate thermal protective clothing, when necessary.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Appearance	Oil, Viscous liquid, Liquid
Color	Amber
Odor	Hydrocarbons Oily
Odor Threshold	No information available
Property	<u>Values</u>
рН	UNKNOWN
Melting / freezing point	No data available

Remarks Method None known None known





Boiling point / boiling range	No data available	None known
Flash Point	149 C / 300 F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity(H ² O=1):	1.08 @ 15.6°C(Typical)	
Water Solubility	Insoluble in water	None known
Dynamic viscosity (cSt 100C)	4.91	None known
Dynamic viscosity (cSt 40C)	32.7	
Explosive properties	No data available	
Oxidizing Properties	No data available	
Density (lbs./gal):	9.08 to 9.33	
Other Information		
Softening Point	No data available	
VOC Content (%)	No data available	

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Oxidizing agent.

Hazardous Decomposition Products

May cause dense smoke, oxides of carbon, hydrogen chloride, nitrogen, sulfur, and calcium.

11. TOXICOLOGICAL INFORMATION

10. STABILITY AND REACTIVITY

Information on likely routes of exposure

Product Information

No adverse effects due to inhalation are expected.
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.
Specific test data for the substance or mixture is not available.





Component Information

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

CarcinogenicityThe table below indicates whether each agency has listed any ingredient as a carcinogen.
The classification pertaining to the chlorinated paraffin is applicable to commercial
chlorinated paraffin of average carbon chain-lengths of C12. The chlorinated paraffin
present in this product is a chlorinated paraffin of a longer carbon chain-length, which is
considered an IARC Class 3 for carcinogenicity (limited evidence). Petroleum products are
known to cause cancer because of carcinogenic components (e.g. benzene). These
carcinogenic components may be removed during the refinement process.

Chemical Name	ACGIH	IARC	NTP	OSHA
Supplier Trade Secret				
Petroleum distillates, hydro treated heavy paraffinic 64742-54-7				

ACGIH (American Conference of Governmental Industrial Hygienists) This product is not listed as carcinogenic.

IARC (International Agency for Research on Cancer)

The International Agency for research on cancer had concluded that highly or severely refined light and middle distillates are Group 3 substances, "not classifiable as to their carcinogenicity to humans," based on inadequate.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

This product is not listed as carcinogenic.

- **Reproductive Toxicity** May cause harm to breastfed babies.
- STOT single exposure No information available.
- STOT repeated exposure No information available.

Chronic Toxicity Avoid repeated exposure. Prolonged exposure may cause chronic effects.

 Target Organ Effects
 Respiratory system. Eyes. Skin. Gastrointestinal tract (GI).

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document Not applicable ATE mix (oral) 1,135,135.00





12. ECOLOGICAL INFORMATION

Eco toxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Supplier Trade Secret		96h LC50: > 300 mg/L (Lepomis macrochirus) 96h LC50: > 100 mg/L (Pimephales promelas) 96h LC50: 94.5 - 271 mg/L (Oncorhynchus mykiss) 96h LC50: > 0.1 mg/L (Lepomis macrochirus) 96h LC50: > 0.0109 mg/L (Oncorhynchus mykiss)		24h EC50: = 102 mg/L
Petroleum distillates, hydro treated heavy paraffinic 64742-54-7		96h LC50: > 5000 mg/L (Oncorhynchus mykiss)		48h EC50: > 1000 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Log Pow	Chemical Name
6	Supplier Trade Secret
6	Supplier Trade Secret

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 221





14. TRANSPORT INFORMATION

DOT Proper Shipping Name Hazard Class TDG MEX	Non-regulated Non-regulated N/A Not regulated Not regulated
ICAO	Not regulated
IATA	Not regulated
Proper Shipping Name	Non-regulated
Hazard Class	N/A
IMDG/IMO	UN3082
UN proper shipping name	Environmentally hazardous substances, liquid, n.o.s. (Alkanes, C14-17,Chloro)
Transport hazard class(es)	
Class	9
Subsidiary risk	
Label(s)	9
Packing group	III
RID	Not regulated
ADR	Not regulated
ADN	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA DSL Complies All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory. **DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List.

US Federal Regulations

All components are on the U.S. EPA TSCA Inventory List. This product is a Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

No No No

No

SARA 311/312 Hazard Categories	
Acute Health Hazard	
Chronic Health Hazard	
Fire Hazard	
Sudden release of pressure hazard	
Reactive Hazard	

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive





Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

OSHA Specifically Regulated Substances(29 CFR 1910.1001-1050)

Not Listed

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	

U.S. State Right-to-Know Regulations

International Regulations

Mexico National occupational exposure limits

Canada WHMIS Hazard Class Non-controlled						
16. OTHER INFORMATION						
NFPA	Health Hazards 1	Flammability 1	Instability 0	Physical and Chemical Hazards -		
HMIS Chronic Hazard Star L	Health Hazards 1*Flammability 1Physical Hazard 0Personal Protection Begend * = Chronic Health Hazard					
Issuing Date	05-May-20	015				

Issuing Date05-May-2015Revision Date22-June-2015Revision NoteNo information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



